



## DECLARATION OF PERFORMANCE

No. 10/2015

1. Unique identification code of the product-type:

**Aluminium\_Konin\_5052**

2. Intended use or uses:

**Intended for internal and external loaded construction elements of buildings**

3. Manufacturer:

**Impexmetal S.A. Aluminium Konin ul. Hutnicza 1, 62-510 Konin**

4. System or systems of assessment and verification of constancy of performance:

**System 2+**

5. Harmonised standard:

**EN 15088:2005**

Notified body/ies:

**Zakłady Badań i Atestacji „ZETOM” im. prof. F. Stauba w Katowicach sp. z o.o.,  
No. 1436-CPR-0032**

6. Declared performance: Sheet, plate and strip aluminium alloy EN AW-5052 cold rolled

Essential characteristics	Performance	Harmonised technical specification																																																																																																				
Dimensional tolerances IDT EN 485-4:1993	<p>Thickness tolerances</p> <table border="1"> <thead> <tr> <th colspan="2" rowspan="2">Specified thickness [mm]</th> <th colspan="4">Thickness tolerances [mm]</th> </tr> <tr> <th>Up to and including 1000mm</th> <th>Over 1000mm up to and including 1250mm</th> <th>Over 1250mm up to and including 1600mm</th> <th>Over 1600mm up to and including 2000mm</th> </tr> <tr> <th>over</th> <th>Up to and including</th> <th>mm</th> <th>mm</th> <th>mm</th> <th>mm</th> </tr> </thead> <tbody> <tr> <td>0,20</td> <td>0,4</td> <td>±0,03</td> <td>±0,05</td> <td>±0,06</td> <td>-</td> </tr> <tr> <td>0,4</td> <td>0,5</td> <td>±0,03</td> <td>±0,05</td> <td>±0,06</td> <td>±0,07</td> </tr> <tr> <td>0,5</td> <td>0,6</td> <td>±0,04</td> <td>±0,06</td> <td>±0,07</td> <td>±0,08</td> </tr> <tr> <td>0,6</td> <td>0,8</td> <td>±0,04</td> <td>±0,07</td> <td>±0,08</td> <td>±0,09</td> </tr> <tr> <td>0,8</td> <td>1,0</td> <td>±0,05</td> <td>±0,08</td> <td>±0,09</td> <td>±0,10</td> </tr> <tr> <td>1,0</td> <td>1,2</td> <td>±0,05</td> <td>±0,09</td> <td>±0,10</td> <td>±0,12</td> </tr> <tr> <td>1,2</td> <td>1,5</td> <td>±0,07</td> <td>±0,11</td> <td>±0,12</td> <td>±0,14</td> </tr> <tr> <td>1,5</td> <td>1,8</td> <td>±0,08</td> <td>±0,12</td> <td>±0,13</td> <td>±0,15</td> </tr> <tr> <td>1,8</td> <td>2</td> <td>±0,09</td> <td>±0,13</td> <td>±0,14</td> <td>±0,16</td> </tr> <tr> <td>2</td> <td>2,5</td> <td>±0,10</td> <td>±0,14</td> <td>±0,15</td> <td>±0,17</td> </tr> <tr> <td>2,5</td> <td>3,0</td> <td>±0,11</td> <td>±0,15</td> <td>±0,17</td> <td>±0,19</td> </tr> <tr> <td>3,0</td> <td>3,5</td> <td>±0,12</td> <td>±0,17</td> <td>±0,19</td> <td>±0,20</td> </tr> <tr> <td>3,5</td> <td>4,0</td> <td>±0,15</td> <td>±0,20</td> <td>±0,22</td> <td>±0,23</td> </tr> <tr> <td>4,0</td> <td>5,0</td> <td>±0,18</td> <td>±0,22</td> <td>±0,24</td> <td>±0,25</td> </tr> </tbody> </table> <p>When measuring the thickness, a zone 10mm wide from the edges of the product shall be disregarded.</p>	Specified thickness [mm]		Thickness tolerances [mm]				Up to and including 1000mm	Over 1000mm up to and including 1250mm	Over 1250mm up to and including 1600mm	Over 1600mm up to and including 2000mm	over	Up to and including	mm	mm	mm	mm	0,20	0,4	±0,03	±0,05	±0,06	-	0,4	0,5	±0,03	±0,05	±0,06	±0,07	0,5	0,6	±0,04	±0,06	±0,07	±0,08	0,6	0,8	±0,04	±0,07	±0,08	±0,09	0,8	1,0	±0,05	±0,08	±0,09	±0,10	1,0	1,2	±0,05	±0,09	±0,10	±0,12	1,2	1,5	±0,07	±0,11	±0,12	±0,14	1,5	1,8	±0,08	±0,12	±0,13	±0,15	1,8	2	±0,09	±0,13	±0,14	±0,16	2	2,5	±0,10	±0,14	±0,15	±0,17	2,5	3,0	±0,11	±0,15	±0,17	±0,19	3,0	3,5	±0,12	±0,17	±0,19	±0,20	3,5	4,0	±0,15	±0,20	±0,22	±0,23	4,0	5,0	±0,18	±0,22	±0,24	±0,25	EN 15088:2005
Specified thickness [mm]				Thickness tolerances [mm]																																																																																																		
		Up to and including 1000mm	Over 1000mm up to and including 1250mm	Over 1250mm up to and including 1600mm	Over 1600mm up to and including 2000mm																																																																																																	
over	Up to and including	mm	mm	mm	mm																																																																																																	
0,20	0,4	±0,03	±0,05	±0,06	-																																																																																																	
0,4	0,5	±0,03	±0,05	±0,06	±0,07																																																																																																	
0,5	0,6	±0,04	±0,06	±0,07	±0,08																																																																																																	
0,6	0,8	±0,04	±0,07	±0,08	±0,09																																																																																																	
0,8	1,0	±0,05	±0,08	±0,09	±0,10																																																																																																	
1,0	1,2	±0,05	±0,09	±0,10	±0,12																																																																																																	
1,2	1,5	±0,07	±0,11	±0,12	±0,14																																																																																																	
1,5	1,8	±0,08	±0,12	±0,13	±0,15																																																																																																	
1,8	2	±0,09	±0,13	±0,14	±0,16																																																																																																	
2	2,5	±0,10	±0,14	±0,15	±0,17																																																																																																	
2,5	3,0	±0,11	±0,15	±0,17	±0,19																																																																																																	
3,0	3,5	±0,12	±0,17	±0,19	±0,20																																																																																																	
3,5	4,0	±0,15	±0,20	±0,22	±0,23																																																																																																	
4,0	5,0	±0,18	±0,22	±0,24	±0,25																																																																																																	



Essential characteristics	Performance										Harmonised technical specification
<b>Dimensional tolerances</b> <b>IDT</b> <b>EN 485-4:1993</b>	<b>Width tolerances for sheet and plate</b>										<b>EN 15088:2005</b>
	Specified thickness [mm]		Width tolerance for specified width [mm]								
	Over	Up to and including	Up to and including 500mm	Over 500mm up to and including 1250mm	Over 1250mm up to and including 2000mm						
	0,20	3,0	+1,5 0	+3 0	+4 0						
3,0	6,0	+3 0	+4 0	+5 0							
6,0	20	+4 0	+5 0	+5 0							
<b>Length tolerances for sheet and plate</b>											
Specified thickness [mm]		Length tolerance for specified length [mm]									
Over	Up to and including	Up to and including 1000mm	Over 1000mm up to and including 2000mm	Over 2000mm up to and including 3000mm	Over 3000mm up to and including 4000mm	Over 5000mm					
0,20	3,0	+3 0	+4 0	+6 0	+8 0	+0,2% of specified length					
3,0	6,0	+4 0	+6 0	+8 0	+10 0						
6,0	20	+6 0	+8 0	+10 0	+10 0						
<b>Width tolerances for strip</b>											
Specified thickness [mm]		Width tolerance for specified width [mm]									
Over	Up to and including	Up to and including 100mm	Over 100mm up to and including 300mm	Over 300mm up to and including 500mm	Over 500mm up to and including 1250mm	Over 1250mm up to and including 1650mm					
0,20	0,6	+0,3 0	+0,4 0	+0,6 0	+1,5 0	+2,5 0					
0,6	1,0	+0,3 0	+0,5 0	+1 0	+1,5 0	+2,5 0					
1,0	2,0	+0,4 0	+0,7 0	+1,2 0	+2 0	+2,5 0					
2,0	3,0	+1 0	+1 0	+1,5 0	+2 0	+2,5 0					
3,0	5,0	-	+1,5 0	+2 0	+3 0	+3 0					
<b>Mechanical properties</b> <b>IDT</b> <b>EN 485-2:2008</b>	Temper	Specified thickness		Tensile strength R <sub>m</sub>		Yield strength R <sub>p0,2</sub>		Elongation A <sub>50</sub> mm		Bend radius <sub>a</sub>	
		[mm]		[MPa]		[MPa]		[%]		180°	90°
		Over	Up to and including	min	max	min	max	min	max		
	O	0,2	0,5	170	215	65		12		0t	0t
		0,5	1,5	170	215	65		14		0t	0t
		1,5	3,0	170	215	65		16		0,5t	0,5t
		3,0	6,0	170	215	65		18			1,0t
		6,0	12,5	165	215	65		19			2,0t
		12,5	20,0	165	215	65		18			
	H111	0,2	0,5	170	215	65		12		0t	0t
	0,5	1,5	170	215	65		14		0t	0t	
	1,5	3,0	170	215	65		16		0,5t	0,5t	
	3,0	6,0	170	215	65		18			1,0t	
	6,0	12,5	165	215	65		19			2,0t	
	12,5	20,0	165	215	65		18				
H12	0,2	0,5	210	260	160		4				
	0,5	1,5	210	260	160		5				
	1,5	3,0	210	260	160		6				
	3,0	6,0	210	260	160		8				
	6,0	12,5	210	260	160		10				
	12,5	20,0	210	260	160		9				





Essential characteristics	Performance										Harmonised technical specification					
<b>Mechanical properties</b> IDT EN 485-2:2008	Temper	Specified thickness [mm]		Tensile strength Rm [MPa]		Yield strength Rp0,2 [MPa]		Elongation A50 mm [%]		Bend radius <sub>a</sub>		EN 15088:2005				
		Over	Up to and including	min	max	min	max	min	max	180°	90°					
	H14	0,2 0,5 1,5 3,0 6,0 12,5	0,5 1,5 3,0 6,0 12,5 20,0	230 230 230 230 230 230	280 280 280 280 280 280	180 180 180 180 180 180			3 3 4 4 5 5		4					
	H16	0,2 0,5 1,5 3,0	0,5 1,5 3,0 6,0	250 250 250 250	300 300 300 300	210 210 210 210			2 3 3 3							
	H18	0,2 0,5 1,5	0,5 1,5 3,0	270 270 270		240 240 240			1 2 2							
	H22	0,2 0,5 1,5 3,0 6,0 12,5	0,5 1,5 3,0 6,0 12,5 20,0	210 210 210 210 210 210	260 260 260 260 260 260	130 130 130 130 130 130			5 6 7 10 12 12		12			1,5t 1,5t 1,5t	0,5t 1,0t 1,5t 1,5t 2,5t	
	H32	0,2 0,5 1,5 3,0 6,0 12,5	0,5 1,5 3,0 6,0 12,5 20,0	210 210 210 210 210 210	260 260 260 260 260 260	130 130 130 130 130 130			5 6 7 10 12 12		12			1,5t 1,5t 1,5t	0,5t 1,0t 1,5t 1,5t 2,5t	
	H24	0,2 0,5 1,5 3,0 6,0 12,5	0,5 1,5 3,0 6,0 12,5 20,0	230 230 230 230 230 230	280 280 280 280 280 280	150 150 150 150 150 150			4 5 6 7 9 9		9			2,0t 2,0t 2,0t	0,5t 1,5t 2,0t 2,5t 3,0t	
	H34	0,2 0,5 1,5 3,0 6,0 12,5	0,5 1,5 3,0 6,0 12,5 20,0	230 230 230 230 230 230	280 280 280 280 280 280	150 150 150 150 150 150			4 5 6 7 9 9		9			2,0t 2,0t 2,0t	0,5t 1,5t 2,0t 2,5t 3,0t	
	H26	0,2 0,5 1,5 3,0	0,5 1,5 3,0 6,0	250 250 250 250	300 300 300 300	180 180 180 180			3 4 5 6						1,5t 2,0t 3,0t 3,5t	
	H36	0,2 0,5 1,5 3,0	0,5 1,5 3,0 6,0	250 250 250 250	300 300 300 300	180 180 180 180			3 4 5 6						1,5t 2,0t 3,0t 3,5t	
	H28	0,2 0,5 1,5	0,5 1,5 3,0	270 270 270		210 210 210			3 3 4							
	H38	0,2 0,5 1,5	0,5 1,5 3,0	270 270 270		210 210 210			3 3 4							

  

<b>Weldability</b> IDT EN 1999-1-1:2007 + A1:2009	Class I											
--	---------	--	--	--	--	--	--	--	--	--	--	--

  

Bendability	Alloy	Temper				
		O H111	H12 H22 H32	H14 H24 H34	H16 H26 H36	H18 H28 H38
	EN AW-5052	-	B2	B2	B2	B2



Essential characteristics	Performance	Harmonised technical specification
Fatigue strength	NPD	EN 15088:2005
Dangerous substances IDT EN 573-3:2009	No	
Durability rating IDT EN 1999-1-1:2007 + A1:2009	Class A	

10. The performance of the product identified above is in conformity with the declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Robert Jeżak  
w Konin dnia 16 lutego 2015r

.....